

EFFECT OF SECONDARY ELECTRON EMISSION ON SUBNANOSECOND BREAKDOWN IN HIGH-VOLTAGE PULSE DISCHARGE

I.V. Schweigert¹, A.L. Alexandrov¹,

P. Gugin², M. Lavrukhin², P.A. Bokhan², Dm.E. Zakrevsky²

¹*Khrstianovich Institute of Theoretical and Applied Mechanics, Novosibirsk, Russia*

²*Rzhanov Institute of Semiconductor Physics, Novosibirsk 630090, Russia*

A subnanosecond breakdown in high-voltage pulse discharge is studied in experiment and in kinetic simulations for mid-high pressure in helium. It is shown that the characteristic time of the current growth can be controlled by the secondary electron emission. We test the influence of secondary electron yield on plasma parameters for three types of cathodes made from titanium, silicon carbide and Cu Al Mg-alloy. By changing the pulse voltage amplitude and gas pressure, the area of existence of subnanosecond breakdown is identified.

Recently serious attention is paid to the study of phenomena of subnanosecond current development in discharge in high-electric fields at mid- and high-pressures. We study the breakdown development in the high voltage discharge in the experiment and in PIC MCC simulations, for cathodes made from 3 different materials with enhanced secondary electron emission yield. Our purpose is to find a way to decrease the breakdown time by testing different cathode materials and changing the gas pressure and voltage. The breakdown in the high-voltage pulse discharge in helium is studied in the experimental cell with two round cathodes placed 6 mm apart. A mesh-anode is placed between the cathodes. The pulse voltage is applied to both cathodes and two opposite electron beams are generated due to cathode emission. The voltage amplitude U ranges from 4 kV to 12 kV and $P=10-35$ Torr. The cathodes are symmetrically connected to the external low-inductance circuit and the mesh-anode is grounded. The pulse shape is registered with the low-inductive resistive divider using oscilloscope Tektronix DPO 70804C with a bandwidth of 8 GHz. The experimental details were described in [1]. In the experiments, the cathodes made from titanium (Ti), silicon carbide (SiC), and CuAlMg alloy were tested. All these materials have large SEE coefficient γ_e , but the dependence of γ_e from the electron energy is different. In our simulations, we solve Boltzmann equations for electrons, ions and fast neutral atoms. Poisson equation describes the electric potential. The details of the model can be found in [2,3]. The record observed switching time for SiC and CuAlMg-alloy is $\tau_s < 0.4$ ns and for Ti is 4-5 times larger. In conclusion, there is a specific range of discharge parameters, 5-10 kV and $P=15-35$ Torr, within that the record switching time $\tau_s < 1$ ns can be achieved.

REFERENCES

- [1] P.A. Bokhan et al 2016 *In: Generation of runaway electron beams and x-rays in high pressure gases*, Nova Science Publishers Inc, NY (2016) p. 221.
- [2] I.V. Schweigert et al. *Phys.Rev.E* **90** (2014) 051101(R);
- [3] I.V. Schweigert et al. *Plasma Sources Sci. Technol.* **24** (2015) 044005.