

Seismic-scale petrophysical interpretation and gas-volume estimation from simultaneous impedance inversion

Wollner U., Arevalo-Lopez H., Dvorkin J.
Kazan Federal University, 420008, Kremlevskaya 18, Kazan, Russia

Abstract

© 2017 by The Society of Exploration Geophysicists. Simultaneous impedance inversion was performed to obtain the seismic-scale P- and S-wave impedances as well as the bulk density volumes from seismic angle stacks at a siliciclastic turbidite offshore gas reservoir. To translate these variables into seismic-scale total porosity (ϕ), clay content, and water saturation (S_w), we used a deterministic rock-physics model established at the well. A crucial input into this model is the bulk modulus (K_f) of the brine/gas system. We need to link it to S_w at the seismic scale. This link can be one of simple mixing laws, such as harmonic and arithmetic. Alternately, it can be derived at the well by using upscaled variables and ensuring that they obey the well-data-driven rock-physics model. These different K_f - S_w relations produce different interpretations for ϕ and S_w thus allowing one to assess the variability in the estimates of the gas volume in place that is proportional to the product of ϕ and $(1 - S_w)$.

<http://dx.doi.org/10.1190/tle36110910.1>

Keywords

Rock physics

References

- [1] Angeleri, G. P., and R. Carpi, 1982, Porosity prediction from seismic data: *Geophysical Prospecting*, 30, no. 5, 580-607, <https://doi.org/10.1111/j.1365-2478.1982.tb01328.x>.
- [2] Arévalo-López, H. S., and J. P. Dvorkin, 2016, Porosity, mineralogy, and pore fluid from simultaneous impedance inversion: *The Leading Edge*, 35, no. 5, 423-429, <https://doi.org/10.1190/tle35050423.1>.
- [3] Arévalo-López, H. S., and J. P. Dvorkin, 2017, Simultaneous impedance inversion and interpretation for an offshore turbiditic reservoir: *Interpretation*, 5, no. 3, SL9-SL23, <https://doi.org/10.1190/INT-2016-0192.1>.
- [4] Avseth, P., 2000, Combining rock physics and sedimentology for seismic reservoir characterization in North Sea turbidite systems: PhD Thesis, Stanford University.
- [5] Bachrach, R., 2006, Joint estimation of porosity and saturation using stochastic rock-physics modeling: *Geophysics*, 71, no. 5, O53-O63, <https://doi.org/10.1190/1.2235991>.
- [6] Backus, G. E., 1962, Long-wave elastic anisotropy produced by horizontal layering: *Journal of Geophysical Research*, 67, no. 11, 4427-4440, <https://doi.org/10.1029/JZ067i011p04427>.
- [7] Brie, A., F. Pampuri, A. F. Marsala, and O. Meazza, 1995, Shear sonic interpretation in gas-bearing sands: SPE Annual Technical Conference and Exhibition, 701-710, <https://doi.org/10.2118/30595-MS>.
- [8] Cadoret, T., 1993, Effet de la saturation eau/gaz sur les propriétés acoustiques des roches: PhD Thesis, University of Paris.

- [9] Dolberg, D. M., J. Helgesen, T. H. Hanssen, I. Magnus, G. Saigal, and B. K. Pedersen, 2000, Porosity prediction from seismic inversion, Lavrans Field, Halten Terrace, Norway: *The Leading Edge*, 19, no. 4, 392-399, <https://doi.org/10.1190/1.1438618>.
- [10] Domenico, S. N., 1976, Effect of brine-gas mixture on velocity in an unconsolidated sand reservoir: *Geophysics*, 41, no. 5, 882-894, <https://doi.org/10.1190/1.1440670>.
- [11] Dvorkin, J., and U. Wollner, 2017, Rock-physics transforms and scale of investigation: *Geophysics*, 82, no. 3, MR75-MR88, <https://doi.org/10.1190/geo2016-0422.1>.
- [12] Eidsvik, J., P. Avseth, H. Omre, T. Mukerji, and G. Mavko, 2004, Stochastic reservoir characterization using prestack seismic data: *Geophysics*, 69, no. 4, 978-993, <https://doi.org/10.1190/1.1778241>.
- [13] Gassmann, F., 1951, Über die elastizität poröser medien: *Vierteljahrsschrift der Naturforschenden Gesellschaft in Zürich*, 96, 1-23.
- [14] Grana, D., and E. Della Rossa, 2010, Probabilistic petrophysical-properties estimation integrating statistical rock physics with seismic inversion: *Geophysics*, 75, no. 3, O21-O37, <https://doi.org/10.1190/1.3386676>.
- [15] Jones, C., J. Selvage, R. Ghosh, and D. Bright, 2015, Enabling interpreters to use seismic image uncertainty measured from common image gathers: 77th Conference and Exhibition, EAGE, Extended Abstracts, <https://doi.org/10.3997/2214-4609.201412611>.
- [16] Marion, D., and D. Jizba, 1997, Acoustic properties of carbonate rocks: Use in quantitative interpretation of sonic and seismic measurements, in I. Palaz, and K. J. Marfurt, eds., *Carbonate seismology*: SEG, 75-94, <https://doi.org/10.1190/1.9781560802099.ch5>.
- [17] Mavko, G., C. Chan, and T. Mukerji, 1995, Fluid substitution: Estimating changes in V_p without knowing V_s : *Geophysics*, 60, no. 6, 1750-1755, <https://doi.org/10.1190/1.1443908>.
- [18] Mukerji, T., A. Jørstad, P. Avseth, G. Mavko, and J. R. Granli, 2001, Mapping lithofacies and pore-fluid probabilities in a North Sea reservoir: Seismic inversions and statistical rock physics: *Geophysics*, 66, no. 4, 988-1001, <https://doi.org/10.1190/1.1487078>.
- [19] Sams, M. S., and D. Saussus, 2010, Comparison of lithology and net pay uncertainty between deterministic and geostatistical inversion workflows: *First Break*, 28, no. 2, 35-44, <https://doi.org/10.3997/1365-2397.2010005>.
- [20] Sengupta, M., and R. Bachrach, 2007, Uncertainty in seismic-based pay volume estimation: Analysis using rock physics and Bayesian statistics: *The Leading Edge*, 26, no. 2, 184-189, <https://doi.org/10.1190/1.2542449>.
- [21] Spikes, K., T. Mukerji, J. Dvorkin, and G. Mavko, 2007, Probabilistic seismic inversion based on rock-physics models: *Geophysics*, 72, no. 5, R87-R97, <https://doi.org/10.1190/1.2760162>.
- [22] Wollner, U., Y. Yang, and J. P. Dvorkin, 2017, Rock-physics diagnostics of an offshore gas field: *Geophysics*, 82, no. 4, MR121-MR132, <https://doi.org/10.1190/geo2016-0390.1>.