

# Steady Darcian Flow in Subsurface Irrigation of Topsoil Impeded by a Substratum: Kornev-Riesenkampf-Philip Legacies Revisited

Obnosov Y., Kacimov A.

Kazan Federal University, 420008, Kremlevskaya 18, Kazan, Russia

---

## Abstract

Copyright © 2018 John Wiley & Sons, Ltd. Flows in homogeneous topsoils with a subjacent substratum or horizontal groundwater table generated by line-point emitters are studied and tracked back to the Kornev method of subsurface irrigation. Laplace's equation governs flow in a saturated or tension-saturated hat-shaped zone subtended by the substratum, provided pressure in a porous pipe or mole hole is positive. For low capillarity a free surface (phreatic line or capillary fringe) and a layer-substratum interface of a constant vertical component of velocity bound the flow domain. The free surface is found for various values of source strengths, emitter elevation above the substratum and the ratio of hydraulic conductivities of the topsoil and substratum. Subcritical and supercritical regimes are distinguished. In the limit of an impermeable substratum, the Riesenkampf solution for a line source is analysed. In soils of high capillarity, the J.R. Philip model of a point source and 'exponential mirror principle' give a series solution for a vertical array of alternating sources and sinks. Four topological situations emerge, depending on the layer thicknesses, topsoil potential, source depths strengths, saturated conductivity and sorptive number. The point source, groundwater table and soil surface are hydrologically intertwined, with formation of dividing surfaces (separatrices) and critical lines. Copyright © 2018 John Wiley & Sons, Ltd.

<http://dx.doi.org/10.1002/ird.2220>

---

## Keywords

advective-dispersion equation, emitter, Kirchhoff potential, Laplace's equation, method of images, water productivity

## References

- [1] Al-Ismaily SS, Al-Maktoumi AK, Kacimov AR, Al-Saqri SM, Al-Busaidi HA, Al-Haddabi MH. 2013. A morphed block-crack preferential sedimentation: a smart design and evolution in nature. *Hydrological Sciences Journal* 58(8): 1779-1788. <https://doi.org/10.1080/02626667.2013.838002>
- [2] Al-Maktoumi A, Al-Ismaily S, Kacimov A, Al-Busaidi H, Al-Saqri S, Al-Haddabi M. 2014. Soil substrate as a cascade of capillary barriers for conserving water in a desert environment: lessons learned from arid nature. *Journal of Arid Land* 6(6): 690-703. <https://doi.org/10.1007/s40333-014-0068-7>
- [3] Ayars JE, Fulton A, Taylor B. 2015. Subsurface drip irrigation in California—here to stay? *Agricultural Water Management* 157: 39-47.
- [4] Bobchenko VI. 1957. *Subsurface Irrigation*. Selkhozgiz: Moscow (in Russian).

- [5] Communar G, Friedman SP. 2015. Cylindrically confined flows of water from a point source and to a sink, above a water table. *Vadose Zone Journal* 14(8). <https://doi.org/10.2136/vzj2014.12.0183>
- [6] Dasberg S, Or D. 1999. *Drip Irrigation*. Springer: Berlin.
- [7] Diamantopoulos E, Elmaloglou S. 2012. The effect of drip line placement on soil water dynamics in the case of surface and subsurface drip irrigation. *Irrigation and Drainage* 61: 622-630.
- [8] Ehmke T. 2014. Subsurface drip irrigation: battling drought, water restrictions, and declining groundwater. *Crops & Soils Magazine* 47(4): 4-10.
- [9] El-Nesr MN, Alazba AA, Simunek J. 2014. HYDRUS simulations of the effects of dual-drip subsurface irrigation and a physical barrier on water movement and solute transport in soils. *Irrigation Science* 32: 111-125.
- [10] Emikh VN. 1999. Seepage flow from subsurface sources. *Fluid Dynamics* 34(2): 218-228.
- [11] Gakhov FD. 1966. *Boundary Value Problems*. Pergamon Press: Oxford.
- [12] Gradshteyn IS, Ryzik IM. 1980. *Table of Integrals, Series and Products*. Academic Press: New York.
- [13] Iwama H, Kubota T, Ushiroda T, Osozawa S, Katou H. 1991. Control of soil water potential using negative pressure water circulation technique. *Soil Science and Plant Nutrition* 37(1): 7-14.
- [14] Kacimov AR. 1992. Minimum dimension of total saturation bubble around an isolated source. *Fluid Dynamics* 27: 886-889.
- [15] Kacimov AR, Obnosov YV. 2012. Accumulation of LNAPL on a flat barrier baffling a descending groundwater flow. *Proceedings of the Royal Society of London A* 468(2147): 3667-3684.
- [16] Kacimov AR, Obnosov YV. 2015. An exact analytical solution for steady seepage from a perched aquifer to a low-permeable sublayer: Kirkham-Brock's legacy revisited. *Water Resources Research* 51: 3093-3107. <https://doi.org/10.1002/2014WR016304>
- [17] Kacimov AR, Obnosov YV. 2016. Tension-saturated and unsaturated flows from line sources in subsurface irrigation: Riesenkampf's and Philip's solutions revisited. *Water Resources Research* 52(3): 1866-1880.
- [18] Kacimov A, Obnosov Y. 2017. Analytical solution for tension-saturated and unsaturated flow from wicking porous pipes in subsurface irrigation: the Kornev-Philip legacies revisited. *Water Resources Research* 53(3): 2542-2552.
- [19] Kirkham D, Horton R. 1992. The stream function of potential theory for a dual-pipe subirrigation-drainage system. *Water Resources Research* 28(2): 373-387.
- [20] Kornev VG. 1935. *Subsurface Irrigation*. Sel'hozgiz: Moscow and Leningrad (in Russian).
- [21] Lazarovitch N, Šimůnek J, Shani U. 2005. System-dependent boundary condition for water flow from subsurface source. *Soil Science Society of America Journal* 69(1): 46-50.
- [22] Martínez J, Reza J. 2014. Water use efficiency of surface drip irrigation versus an alternative subsurface drip irrigation method. *Journal of Irrigation and Drainage Engineering* 140(10): 04014030. [https://doi.org/10.1061/\(ASCE\)IR.1943-4774.0000745](https://doi.org/10.1061/(ASCE)IR.1943-4774.0000745)
- [23] Maslov BS, Stankevich VS, Cherenok VYA. 1973. *Drainage-wetting Systems*. Kolos: Moscow (in Russian).
- [24] Obnosov YV, Kasimova RG, Kacimov AR. 2011. A well in a 'target' stratum of a two-layered formation: the Muskat-Riesenkampf solution revisited. *Transport in Porous Media* 87: 437-457.
- [25] Patel N, Rajput TBS. 2008. Dynamics and modeling of soil water under subsurface drip irrigated onion. *Agricultural Water Management* 95(12): 1335-1349.
- [26] Philip JR. 1968. Steady infiltration from buried point sources and spherical cavities. *Water Resources Research* 4: 1039-1047.
- [27] Philip JR. 1989. Multidimensional steady infiltration to a water table. *Water Resources Research* 25: 109-116.
- [28] Philip JR. 1990. How to avoid free boundary problems. In *Free Boundary Problems: Theory and Applications*, vol. 1, Hoffmann KH, Sprekels J (eds). *Research Notes in Mathematics*, vol. 185. Longman: New York; 193-207.
- [29] Philip JR. 1992. What happens near a quasi-linear point source? *Water Resources Research* 28(1): 47-52.
- [30] Polubarinova-Kochina PYA. 1962. *Theory of Ground Water Movement*. Princeton University Press: Princeton. A second edition of the book in Russian was published in 1977, Nauka, Moscow.
- [31] Provenzano G. 2007. Using HYDRUS-2D simulation model to evaluate wetted soil volume in subsurface drip irrigation systems. *Journal of Irrigation and Drainage Engineering ASCE* 133(4): 342-349.
- [32] Raats PAC. 1970. Steady infiltration from line sources and furrows. *Soil Science Society of America Proceedings* 34: 709-714.
- [33] Readigger VP. 1965. *Subsurface Irrigation by Mole Holes*. Kolos: Moscow (in Russian).
- [34] Riesenkampf BK. 1938. *Hydraulics of groundwater*. Part 2. *Transactions of Saratov State University* 14(2): 181-205 (in Russian).
- [35] Shani U, Xue S, Gordin-Katz R, Warrick AW. 1996. Soil-limiting flow from subsurface emitters. I: Pressure measurements. *Journal of Irrigation and Drainage Engineering ASCE* 122(5): 291-295.

- [36] Šimůnek J, Van Genuchten MT, Šejna M. 2012. The HYDRUS Software Package for Simulating Two-and Three-Dimensional Movement of Water, Heat, and Multiple Solutes in Variably-Saturated Media. Technical manual, version 2. University of California, Riverside.
- [37] Siyal AA, Skaggs TH. 2009. Measured and simulated soil wetting patterns under porous clay pipe sub- surface irrigation. *Agricultural Water Management* 96: 893-904.
- [38] Strack ODL. 1989. *Groundwater Mechanics*. Prentice Hall: Englewood Cliffs.
- [39] Vasil'ev VA. 1955. On the shape of a groundwater mound with infiltration between two drains on an impermeable layer. *Prikladnaya Matematika i Mekhanika (PMM)* 19(1): 106-108 (in Russian).
- [40] Vedernikov VV. 1939. *Theory of Seepage and its Applications to Problems of Irrigation and Drainage*. Gosstroizdat: Moscow and Leningrad (in Russian).
- [41] Warrick AW. 1993. Unsaturated-saturated flow near a quasi-linear line source. *Water Resources Research* 29: 3759-3762.
- [42] Warrick AW, Lomen DO. 1977. Flow from a line source above a shallow water table. *Soil Science Society of America Journal* 41(5): 849-852.
- [43] Warrick AW, Shani U. 1996. Soil-limiting flow from subsurface emitters. II: Effect on uniformity. *Journal of Irrigation and Drainage Engineering ASCE* 122(5): 296-300.
- [44] Wolfram S. 1991. *Mathematica. A System for Doing Mathematics by Computer*. Addison-Wesley: Redwood City.
- [45] Zur B. 1996. Wetted soil volume as a design objective in trickle irrigation. *Irrigation Science* 16: 101-105.