

Formation of the diffusion layer in gas boring

Ilyin V., Sabitov L., Khaibullina A., Ilyin O.

Kazan Federal University, 420008, Kremlevskaya 18, Kazan, Russia

Abstract

© Published under licence by IOP Publishing Ltd. Boriding in powder media is successfully used to increase the life of parts. To increase the depth of the diffusion layer and improve its properties, a method for activating the surface of a saturable part by means of electromechanical processing is proposed. The results on the structure of the resulting layer and its dimensions are presented.

<http://dx.doi.org/10.1088/1757-899X/412/1/012029>

References

- [1] Borisenok GV 1981 Chemical-thermal treatment of metals and alloys: reference book (Moscow: Metallurgy) 424 and others
- [2] Ilyin V K 2004 Restoration and strengthening of details of agricultural machinery by methods of diffusion saturation 297 Diss. the doctors. tech. sciences
- [3] Voroshnin L G and Lyakhovich L S 1978 Borating of steel (Moscow: Metallurgy) 240
- [4] Ivanov S G, Guriev A M, Chernykh E V, Guriev M A, Ivanova T G, Garmaeva I A, Zobnev V V and Gong V 2014 Thermodynamic modeling of reactions in a saturating medium during the diffusion boronization of steels Fundamental problems of modern materials science 11 13-16